




**HIGH PERFORMANCE  
BIFACIAL PERC MONOCRYSTALLINE MODULE**



**RSM120-8-585BMDG-610BMDG**

<b>120 CELL</b> Mono PERC Module	<b>585-610Wp</b> Power Output Range
<b>1500VDC</b> Maximum System Voltage	<b>21.6%</b> Maximum Efficiency

**KEY SALIENT FEATURES**


- Global, Tier 1 bankable brand, with independently certified state-of-the-art automated manufacturing
- Bifacial technology enables additional energy harvesting from rear side (up to 30%)
- Industry leading lowest thermal co-efficient of power
- Industry leading 12 years product warranty
- Excellent low irradiance performance
- Excellent PID resistance
- Positive power tolerance of 0~+3%
- Dual stage 100% EL Inspection warranting defect-free product
- Module Imp binning radically reduces string mismatch losses
- Excellent wind load 2400Pa & snow load 5400Pa under certain installation method
- Comprehensive product and system certification
  - ◆ IEC61215:2016; IEC61730-1/-2:2016;
  - ◆ ISO 9001:2015 Quality Management System
  - ◆ ISO 14001:2015 Environmental Management System
  - ◆ ISO 45001:2018 Occupational Health and Safety Management System





\* As there are different certification requirements in different markets, please contact your local Risen Energy sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

**LINEAR PERFORMANCE WARRANTY**

**12 year Product Warranty / 30 year Linear Power Warranty**



### Dimensions of PV Module Unit: mm



### ELECTRICAL DATA (STC)

Model Number	RSM120-8-580BMDG	RSM120-8-585BMDG	RSM120-8-590BMDG	RSM120-8-595BMDG	RSM120-8-600BMDG	RSM120-8-605BMDG
Rated Power in Watts-Pmax(Wp)	580	585	590	595	600	605
Open Circuit Voltage-Voc(V)	40.90	41.10	41.30	41.50	41.70	41.90
Short Circuit Current-Isc(A)	18.06	18.11	18.16	18.21	18.26	18.32
Maximum Power Voltage-Vmpp(V)	34.04	34.22	34.42	34.60	34.80	34.98
Maximum Power Current-Imp(A)	17.05	17.10	17.15	17.20	17.25	17.30
Module Efficiency (%) ★	20.5	20.7	20.8	21.0	21.2	21.4

STC: Irradiance 1000 W/m<sup>2</sup>, Cell Temperature 25°C, Air Mass AM1.5 according to EN 60904-3.  
Bifacial factor: 70±10(%) ★ Module Efficiency (%): Round-off to the nearest number

### Electrical characteristics with 10% rear side power gain

	644	649	655	660	666	671
Total Equivalent power -Pmax (Wp)	644	649	655	660	666	671
Open Circuit Voltage-Voc(V)	41.10	41.30	41.50	41.70	41.90	42.20
Short Circuit Current-Isc(A)	19.92	19.98	20.03	20.09	20.15	20.21
Maximum Power Voltage-Vmpp(V)	34.22	34.42	34.60	34.80	34.98	35.18
Maximum Power Current-Imp(A)	18.81	18.87	18.92	18.98	19.03	19.09

Rear side power gain: The additional gain from the rear side compared to the power of the front side at the standard test condition. It depends on mounting (structure, height, tilt angle etc.) and albedo of the ground.

### ELECTRICAL DATA (NMOT)

Model Number	RSM120-8-585BMDG	RSM120-8-590BMDG	RSM120-8-595BMDG	RSM120-8-600BMDG	RSM120-8-605BMDG	RSM120-8-610BMDG
Maximum Power-Pmax (Wp)	443.1	447.0	450.7	454.6	458.3	462.2
Open Circuit Voltage-Voc (V)	38.22	38.41	38.60	38.78	38.97	39.25
Short Circuit Current-Isc (A)	14.85	14.89	14.93	14.97	15.02	15.06
Maximum Power Voltage-Vmpp (V)	31.76	31.94	32.11	32.29	32.46	32.65
Maximum Power Current-Imp (A)	13.95	13.99	14.04	14.08	14.12	14.16

NMOT: Irradiance at 800 W/m<sup>2</sup>, Ambient Temperature 20°C, Wind Speed 1 m/s.

### MECHANICAL DATA

Solar cells	Monocrystalline
Cell configuration	120 cells (6×10×6×10)
Module dimensions	2172×1303×33mm
Weight	34.5kg
Superstrate	High Transmission, AR Coated Heat Strengthened Glass
Substrate	Heat Strengthened Glass
Frame	Anodized Aluminium Alloy , Silver Color
J-Box	Potted, IP68, 1500VDC, 3 Schottky bypass diodes
Cables	4.0mm <sup>2</sup> , Positive(+)350mm, Negative(-)230mm (Connector Included )
Connector	Risen Twinsel PV-SY02, IP68



### TEMPERATURE & MAXIMUM RATINGS

Nominal Module Operating Temperature (NMOT)	44°C±2°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	0.04%/°C
Temperature Coefficient of Pmax	-0.34%/°C
Operational Temperature	-40°C~+85°C
Maximum System Voltage	1500VDC
Max Series Fuse Rating	35A
Limiting Reverse Current	35A

### PACKAGING CONFIGURATION

	40ft(HQ)
Number of modules per container	594
Number of modules per pallet	33
Number of pallets per container	18
Packaging box dimensions (LxWxH) in mm	1320×1125×2310
Box gross weight[kg]	1180

CAUTION: READ SAFETY AND INSTALLATION INSTRUCTIONS BEFORE USING THE PRODUCT.



### Our Partners: